

POLYTEX™

230

WARRANTY 10 YEAR UV PERFORMANCE

PREMIUM FIRE RATED ARCHITECTURAL GRADE SHADE FABRIC

150" Width • 8.1 Oz. Per Sq. Yd.



AQUAMARINE



YELLOW



SILVER



SANDSTONE



SLATE



SAGE



BRONZE



RUST



BLACK



MIDNIGHT GREEN



PORCELAIN



CLARET



NAVY BLUE

PREMIUM FIRE RATED ARCHITECTURAL GRADE SHADE FABRIC

Polytex™ is a premium quality knitted monofilament and tape shade fabric purposefully designed for moderate tension and modular shading applications and other shade structures, providing strength and high shade factor in a light weight cloth. It is perfect for use in structures for pools, patios, parking lots, school play areas, anywhere shade and protection for people and property is desired.

- 150" width or 12.5 feet
- 8.1 ounces per square yard
- Exceptionally light weight, yet extremely strong
- Widely preferred for commercial and residential shade applications
- Flame retardant to California State Fire Marshal 13115; NFPA-701-1999; ASTM-E-84, Class A Building Material
- UVA & UVB protection greater than 95%
- Put up on 100 foot rolls

Breaking force (AS 2001.2.3.1 - 2001)

Warp:
134 lbs.

Weft:
454 lbs.

Breaking extension (AS 2001.2.3.1 - 2001)

86.1%

56.2%

Tear resistance (AS 2001.2.10 - 1986)

24 lbs.

42 lbs.

Bursting force (AS 2001.2.19 - 1988)

Face

372 lbs.

Color Range	UVA	UVB	Mean UPF	Shade Factor
Aquamarine	92.5%	92.6%	14	66%
Black	96.9%	96.9%	33	97%
Bronze	90.4%	90.0%	10	80%
Claret	89.6%	91.7%	11	80%
Midnight Green	94.9%	94.8%	19	85%
Navy Blue	95.7%	95.9%	25	87%
Porcelain	94.9%	95.7%	23	73%
Rust	83.6%	83.7%	6	67%
Sage	92.4%	92.4%	13	86%
Sandstone	92.4%	92.4%	13	72%
Silver	84.5%	84.8%	7	87%
Slate	94.2%	94.3%	18	90%
Yellow	94.0%	94.2%	17	69%

10 YEAR ULTRAVIOLET PERFORMANCE WARRANTY, Conditions Apply

*UVA and UVB are measures of Ultra Violet Radiation that has been shown to be harmful and excessive exposure can lead to the development of skin cancer.